

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate no.:  
**MEDB00008YG**

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

## This is to certify:

**that the Surface materials and floor coverings with low flame-spread characteristics: Adhesives used in the construction of "A", "B" & "C" class divisions**

with type designation(s)  
**MD-Megabond 3000**

issued to

**Marston-Domsel GmbH**  
**Zülpich, Nordrhein-Westfalen, Germany**

is found to comply with the requirements in the following Regulations/Standards:

Regulation **(EU) 2023/1667**,

**item No. MED/3.18e. SOLAS 74, Reg. II-2/3, II-2/5, II-2/9 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code**


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2029-07-01**.

Issued at **Hamburg** on **2024-07-02**

DNV local unit:  
**Essen**

Approval Engineer:  
**Timo Linn**



Notified Body  
No.: **0098**



for **DNV SE**

Digitally Signed By:  
**Christine Mydlak-Röder**  
Location: **DNV Hamburg,**  
**Germany**

**Mydlak-Röder, Christine**  
**Head of Notified Body**

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

**LEGAL DISCLAIMER:** Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

"MD Megabond 3000"

Two component adhesive (mixed ratio 10/1) designated MD Megabond 3000.

Applied maximum amount of wet adhesive: 100 g/m<sup>2</sup>

Density: 0.96 g/cm<sup>3</sup> (white) / 1.07g/cm<sup>3</sup> (black)

## Application/Limitation

Approved for use as adhesive with low flame spread characteristics, not generating excessive quantities of smoke nor toxic products in fire.

The product satisfies the requirement for maximum calorific value (ref. SOLAS Chapter II-2, Reg 5.3.2.2) without further testing.

Each product is to be supplied with its manual for installation and use.

## Type Examination documentation

Test report No. PFB10629C dated 20 March 2024 from DBI Danish Institute of Fire and Security Technology, Denmark.

Technical data sheet "MD MEGABOND 3000 10:1" dated 29 December 2016 from Marston-Domsel GmbH.

## Tests carried out

Tested according to IMO 2010 FTP Code Part 5 and Annex 2 item 2.2 and item 2.3.

## Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation and MED Mark of Conformity.